



# COMPENSYL

## HYDRAULIC FLUID

<b>Product description</b>	COMPENSYL is a special mineral liquid ideal for the maintenance and functioning of hydraulic shock absorbers, jacks, buckets, lifts, cranes...
<b>Properties</b>	<ul style="list-style-type: none"><li>• Exceptional viscosity properties - Does not breakdown under extreme temperatures.</li><li>• Harmless to metals and fibre or synthetic seals (Aniline point 91°C).</li><li>• Zero sulphur content.</li><li>• Protects against corrosion.</li><li>• Exceptional resistance to oxidation and shear - No deposits even after months of use.</li><li>• Extreme pressure and anti-wear properties - Meets the most severe demands.</li><li>• Excellent lubricating properties - Minimises friction.</li><li>• Anti-foaming additive prevents the formation of harmful foams, which affect the proper function of hydraulic systems.</li><li>• Very quick deaeration properties.</li></ul>
<b>Basic uses</b>	<ul style="list-style-type: none"><li>• Exterior</li><li>• Special mineral liquid:<ul style="list-style-type: none"><li>- Hydraulics</li><li>- Shock absorbers</li><li>- Jacks</li><li>- Pumps</li><li>- Trucks</li></ul></li></ul>
<b>Technical data</b>	<p><b>Viscosity (cSt):</b></p> <ul style="list-style-type: none"><li>- 50.20 @ 20°C</li><li>- 20.90 @ 40°C</li><li>- 4.24 @ 100°C</li></ul> <p><b>Grade ISO:</b> 22SAE10.</p> <p><b>Viscosity index:</b> 107 (NFT 60-136).</p> <p><b>Flow point:</b> - 36°C (allowing use at very low temperatures).</p> <p><b>Working temperature range:</b> - 25°C to + 65°C.</p> <p><b>Flammability (VO):</b> + 197°C (avoids danger at normal temperatures as well as loss due to product evaporation).</p> <p><b>Container size:</b> Aerosol 200ml &amp; 400ml, 250ml, 2L, 5L, 20L, 60L.</p>
<b>General information</b>	<p>Every care is taken to ensure that the information provided in this technical data sheet is accurate. OWATROL International is unable to guarantee results as we have no control over the conditions under which our products are applied. For further advice and information please contact our technical department by email at <a href="mailto:info@owatrol.com">info@owatrol.com</a> or the local OWATROL Agent for your country. The information above is correct at the date of issue.</p> <p>All other OWATROL products named in this document should be used as per label instructions and the technical data sheet.</p>
<b>Safety</b>	Refer to the safety data sheet (MSDS) available at <a href="http://www.owatrol.com">www.owatrol.com</a> and text on the packaging. Keep out of the reach of children.
<b>Issue date</b>	November 2014.

