



PRIMISOL MASKING PRIMER

| | |
|----------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Description | PRIMISOL is a water based concealing primer for the masking and blocking of light surface stains. |
| Properties | <ul style="list-style-type: none"> • Masks and hides surface stains – Soot, Smoke, Water • Limits tannin stains on wood. • Prevents bleeding of the stain into the finish. • Evens out the porosity of the surface – Gives uniform appearance to the finish coat. |
| Basic uses | <ul style="list-style-type: none"> • Interior. • May be used externally if sheltered by roofing. • Smooth surfaces – Varnish, Paint etc. • Walls Ceilings, Doors, Cabinets, Furniture.... • Wood, Concrete, MDF, Plywood, Plaster, Stone.... |
| Technical data | <p>Classification: Family I - Class 7b2 (NF T 36-005).</p> <p>Finish: Matt.</p> <p>Vehicle Type: Acrylic resins.</p> <p>Solvent Type: Water.</p> <p>Specific Gravity at +25°C (68°F): 1.35 ±0.05.</p> <p>Physical State: Liquid.</p> <p>Solid Content by Weight: 58% ±2.</p> <p>Solid Content by Volume: 38% ±2.</p> <p>Shelf Life: 1 year minimum in original unopened packaging.</p> <p>Flammability: Not classed as flammable.</p> <p>Container Size: 5L. 15L.</p> <p>Colour: White.</p> <p>Drying Time at 20°C (68°F) & 65% RH:</p> <ul style="list-style-type: none"> • Dry: 1 hour. • Recoat: Acrylic (Water based) finishes 6 hours. Oil based finishes 48 hours. <p>VOC: EU limit value for this product (cat A/g): 30g/L (2010). This product contains max 5g/L.</p> |
| Application tools | <p>Brush.</p> <p>Roller.</p> <p>Airless or HVLP (Adjust the material viscosity accordingly – Max 10%).</p> |
| Good application practice | <p>Cover and protect everything you do not wish to coat.</p> <p>Apply between 10°C and 25°C. RH <65%.</p> <p>Do not apply to hot surfaces.</p> |
| Surface preparation | <p>Surfaces must be clean, dry and free of all dust, grease, oil, wax, excessive chalky material and other surface contamination, which may affect adhesion.</p> <p>Remove all loose and flaking material back to a sound surface by sanding and scraping.</p> <p>Sand smooth surfaces to form a key.</p> <p>Wash surface with SOAPCLEAN* or other suitable cleaning agent, NOT washing-up detergent.</p> <p>Treat and remove any mould with a suitable mould killer.</p> <p>Prime high tannin content woods with OWAFILTER* prior to applying PRIMISOL.</p> <p>For unknown or heavy staining use PRIMAPRO*.</p> |

The information presented here is given for information purposes only and does not engage the liability of the manufacturer, as the application of products is not carried out under its control. * Information on the level of omissions of volatile substances in indoor air, presenting a risk of toxicity through inhalation, on a classification scale ranging from A+ (variable omissions) to C (high omissions).

| | |
|----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Application | Use as is. Do not thin. Stir well before and during use. Apply 1 even coat of PRIMISOL. Do Not over apply. Allow to dry. |
| Coverage | 10m ² (107ft ²) per litre per coat. Actual coverage will vary depending on application method, type, texture, age and porosity of the surface. |
| Clean-up | Clean all tools and equipment with soap and water immediately after use. |
| Storage | Store in original container and close lid tightly after use. Keep from freezing and high temperatures. |
| General information | Every care is taken to ensure that the information provided in this technical data sheet is accurate. Owatrol International is unable to guarantee results as we have no control over the conditions under which our products are applied. For further advice and information please contact our technical department by email at info@owatrol.com or the local Owatrol Agent for your country. The information above is correct at the date of issue. All other OWATROL products named in this document should be used as per label instructions and the relevant Technical Data Sheet. |
| Safety | Refer to the safety data sheet (MSDS) available at www.owatrol.com and text on the packaging. Keep out of the reach of children. |
| Issue Date | November 2018 |

* Same Manufacturer

OWATROL INTERNATIONAL
Barcelona – Spain
Tel: +34 93 125 88 68
Fax: +34 93 106 02 13



Discover all our solutions at:
www.owatrol.com