
























# OWATROL® AGP

## NON-FEROUS METAL AND PLASTIC PAINT

<b>Description</b>	OWATROL® AGP is a waterbased satin finish for the coating of smooth and difficult surfaces. Having exceptional adhesion properties OWATROL® AGP requires no separate primer.														
<b>Properties</b>	<ul style="list-style-type: none"> <li>• Excellent adhesion on difficult to paint surfaces.</li> <li>• No separate primer required.</li> <li>• White Tintable to create pastel colours.</li> <li>• 7 year guarantee against chipping.</li> <li>• Protects and restores weather beaten plastic and metals.</li> </ul>														
<b>Basic uses</b>	<ul style="list-style-type: none"> <li>• Interior and Exterior.</li> <li>• Horizontal and vertical surfaces.</li> <li>• Non-ferrous metals – Aluminium, Zinc, Galvanised Steel...</li> <li>• Smooth and glossy surfaces – Hard Plastic, PVC, pre-Painted metals...</li> <li>• Guttering, Cladding, Garage Doors, uPVC Joinery...</li> </ul>														
<b>Technical data</b>	<p><b>Finish:</b> Satin.  <b>Vehicle Type:</b> Acrylic resins.  <b>Solvent Type:</b> Water.  <b>Specific Gravity at 25°C (77°F):</b> 1.13 to 1.30g/cm<sup>3</sup> ± 0.02 depending on colour.  <b>Viscosity at 20°C (68°F):</b> 12-15 poise depending on colour.  <b>Flash point:</b> Not applicable.  <b>Shelf Life:</b> 1 Year minimum in original unopened packaging.  <b>Container Size:</b> 500mL.</p> <p><b>Colours:</b></p> <table border="0" style="width: 100%; text-align: center;"> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>White</td> <td>Sand</td> <td>Lightly Grey</td> <td>Dark Grey</td> <td>Bordeaux</td> <td>Dark Green</td> <td>Black</td> </tr> </table> <p>White may be tinted with universal colourants (3% Max).</p> <p><b>Drying times (at 20°C (68°F) &amp; 50% RH):</b>  <b>Touch Dry:</b> 2 hours.  <b>Re-coat:</b> 6 hours.  <b>Hard Dry:</b> 3 days.  Drying times dependant on temperature and humidity.  <b>VOC:</b> EU limit value for this product (cat A/i) 140 g/L (2010). This product contains max 15 g/L.</p>								White	Sand	Lightly Grey	Dark Grey	Bordeaux	Dark Green	Black
															
White	Sand	Lightly Grey	Dark Grey	Bordeaux	Dark Green	Black									
<b>Application tools</b>	Synthetic Brush. Roller. Spray.														
<b>Good application practice</b>	<p>Before starting, test colour choice on a small area. Allow to dry to determine final colour.  Cover everything you do not wish to coat.  Apply between 10°C (50°F) and 25°C (77°F).  Do not apply in direct sunlight or to hot surfaces.  Do not apply if cold and/or wet weather is expected within 24 hours.  Surface must be fully dry before applying OWATROL® AGP.  Do not over apply. Applying several thin coats will aid flexibility and improve the finish.  For spray application OWATROL® AGP may be diluted 5% to 10% with water.</p>														
<b>Surface preparation</b>	<p>Surfaces must be clean, dry, in sound condition and free of dirt, grease, grime, wax and other surface contamination including all previous coatings prior to applying OWATROL® AGP.  Clean surface with suitable cleaning agent e.g. PURA-TROL*, Acetone or hot soapy water depending on the substrate.  Depending on the substrate and coating applied strip with DSP 800*, DILUNETT®* or by mechanical abrasion.  Sand glossy and smooth surfaces to form a key.</p>														

<b>Surface preparation</b>	<p><b>Galvanised/Zinc:</b> Depending on condition of the surface (new or weathered) pickle using diluted PURA-TROL* (See (1) below) or a phosphoric solution OR clean using a suitable solvent e.g. Acetone, PURA-TROL*.</p> <p><b>Aluminium:</b> Thoroughly clean surface using a suitable solvent e.g. Acetone, PURA-TROL*. Abraded with 24-120 grit paper compatible with Aluminium. Clean surface of all preparation residue.</p> <p><b>Note:</b> Where the surface is rinsed with water allow to dry 24 to 72 hours before applying OWATROL® AGP*.</p> <p><b>(1) PICKLING SURFACE WITH PURA-TROL*</b> 1 part PURA-TROL* to 5 parts water. Apply by cloth or brush. Leave to work 5-10 minutes. Rinse thoroughly and allow to dry.</p>
<b>Application</b>	Stir product well before and during use. <b>Do not</b> thin. Apply 2 coats allowing drying time between coats.
<b>Coverage</b>	8 to 10m <sup>2</sup> per litre per coat. Actual coverage will vary depending on application method, texture, age and porosity of the surface.
<b>Restrictions</b>	Do Not apply to soft plastic, nylon, polyethylene and polypropylene surfaces. Do not use on garden furniture.
<b>Clean-up</b>	Soap and water.
<b>Storage</b>	Close lid tightly after use and store in original container. Keep from freezing and high temperatures.
<b>Limited warranty</b>	OWATROL® International warrants OWATROL® AGP against chipping for a period of 7 years from the date of purchase when applied to a properly prepared surface and in accordance with the directions given on the label and in this Technical Data sheet. Owatrol International will, at its option, replace the material or refund the purchase price if OWATROL® AGP does not perform as described above. All claims must be made in writing and accompanied by the original proof of purchase.
<b>General Information</b>	Every care is taken to ensure that the information provided in this technical data sheet is accurate. <b>Owatrol International</b> is unable to guarantee results as we have no control over the conditions under which our products are applied. For further advice and information please contact our technical department by email at <a href="mailto:info@owatrol.com">info@owatrol.com</a> or the local Owatrol Agent for your country. The information above is correct at the date of issue. All other OWATROL products named in this document should be used as per label instructions and the technical data sheet.
<b>Safety</b>	Refer to the safety data sheet (MSDS) available at <a href="http://www.owatrol.com">www.owatrol.com</a> and text on the packaging. Keep out of the reach of children.
<b>Issue date</b>	February 2017

\* Same manufacturer

The information set out cons are purely illustrative and are not the responsibility of the manufacturer, the application of products not made under his supervision.